

MFWD SPECIFICATIONS

	275	295	315	335	365
ENGINE					
Engine Model	Cummins QSL9 (Tier IV Final)				
Displacement	9 L (549 cid)				
Horsepower¹	275 hp (205kW)	295 hp (220 kW)	315 hp (235 kW)	335 hp (250 kW)	365 hp (272 kW)
Power Bulge	8% @ 1,900 rpm	8% @ 1,900 rpm	10% @ 1,900 rpm	10% @ 1,900 rpm	10% @ 1,900 rpm
Peak Horsepower	300 hp (216 kW)	320 hp (239 kW)	340 hp (254 kW)	370 hp (276 kW)	400 hp (298 kW)
PTO hp	220 hp (164 kW)	232 hp (173 kW)	248 hp (185 kW)	268 hp (200 kW)	272 hp (203 kW)
Torque Rise	45% @ 1,500 rpm	34% @ 1,500 rpm	29% @ 1,500 rpm	35% @ 1,500 rpm	31% @ 1,500 rpm
Peak Torque	945 lb-ft (1,282 N·m)	985 lb-ft (1,335 N·m)	995 lb-ft (1,350 N·m)	1,130 lb-ft (1,532 N·m)	1,199 lb-ft (1,626 N·m)
Aspiration	Turbocharged and air-to-air aftercooled				
TRANSMISSION					
Powershift Transmission	16 forward, 9 reverse				
Maximum Speed	25 mph (40 km/h)				
HYDRAULICS					
Type	Closed center load sensing system				
Standard Flow	55 gpm (208 L/min)				
High Flow (optional)	72 gpm (273 L/min)				
Implement Remotes (standard)	4 EHR				
Implement Remotes (optional)	6 EHR				
Maximum System Pressure	2900 psi (200 bar)				
DRAWBAR					
Drawbar (standard)	Category III			Category IV	
Drawbar (optional)	Category IV			-	
3-POINT HITCH & PTO					
3-Point Hitch	Category III / IIIN			Category III / IVN	
PTO (standard)	1,000 rpm			1,000 rpm	
PTO (optional)	540 / 1,000 rpm			-	

MFWD SPECIFICATIONS

	275	295	315	335	365
AXLES					
Front Axle (standard)		Limited slip		Suspended with differential lock	
Front Axle (optional)		Differential lock; Suspended with differential lock		Limited slip; differential lock	
CAB					
Volume			149 cu. ft. (4.22 cu. m)		
Glass			73.5 sq. ft. (6.83 sq. m)		
ELECTRICAL SYSTEM					
Alternator			12V-200 amps		
Batteries			2 12V, 950 CCA		
FUEL SYSTEM					
Fuel Capacity			162 U.S. gal (613 L)		
DEF Capacity			9 U.S. gal (34 L)		
WEIGHTS & DIMENSIONS					
Base Tractor Weight²		27,660 lbs (12,546 kg)		28,060 lbs (12,728 kg)	
Recommended Operating GVW	28,600 lbs (12,973 kg)	29,762 lbs (13,500 kg)	31,173 lbs (14,140 kg)	33,950 lbs (15,400 kg)	35,400 lbs (16,057 kg)
Wheelbase		124.6" (3,165 mm)		128.95" (3,275 mm)	

¹SAE horsepower measured @ 2,100 rpm

²Estimated weight based on standard drawbar, no fuel, no operator, no ballast, no additional equipment

NOTE: Specification are correct at time of publishing and are subject to change